

More Water for Less Cost.

HC 0.8-1.6mm | NC 0.8-1.6mm

Filtralite® Pure filter media is a highly porous engineered ceramic media that offers significantly better performance than traditional filter media. The increased surface area of Filtralite® allows larger volumes of water to be filtered through the same volume of media with multiple operational benefits. Compared to traditional filter media like sand and anthracite, Filtralite® has much higher porosity which gives:

- ✓ Effective iron removal
- ✓ Lower backwash rates
- ✓ Longer filter runs between backwashes
- ✓ Higher storage capacity
- ✓ Lower initial head loss
- ✓ Slower head loss build up
- ✓ Lifetime of over 20 years

These advantages lead to reduced energy and water consumption, as well as higher water production for drinking water.



Pentair Polyglass Vessels
VSSF-1 & VSSF-2

VERTICAL SERIES SMALL SYSTEM FILTER SPECIFICATIONS

Vessel Diameter and Height:

VSSF-1: 12"x52"	VSSF-4: 24"x72"
VSSF-2: 16"x65"	VSSF-5: 30"x72"
VSSF-3: 21"x62"	VSSF-6: 30"x72"

Plumbing Connections:

VSSF-1: 3/4"	VSSF-4: 3/4"
VSSF-2: 3/4"	VSSF-5: 3/4"
VSSF-3: 3/4"	VSSF-6: 3/4"



Pentair Fleck 5812 Control Valve
and SXT Timer



Pentair Composite Vessels
VSSF-3 – VSSF-6



Certified to
EN 12905



Certified to
NSF/ANSI

(306) 986-4499 sapphiresales@delco-water.com

www.delco-water.com