

Membrane Quantity	Permeate Flow Range	Min/Max Operating Pressure	Recovery	Dimensions Height   Width   Depth	Shipping Weight
4	2.35 - 3.55 USGPM	30 - 170 psi	50-80%	Inches: 60   28   29 Mm: 1524   711   744	250 lbs (113 kgs)

### Water Quality Recommendations

TDS Maximum: 3000 mg/L  
Chloride Maximum: 500 mg/L



*\* Expected operating pressures and flow set points can be shared if lab water quality is provided. Predicted system flow rate is based on membrane manufacturer specifications and nominal conditions. Membrane production varies with water quality, operating pressure, temperature, pH, and recovery. Anti-scalant chemical injection required.*

### ADDITIONAL ENHANCEMENTS

- Permeate Flush
- Re-pressurization System
- Granular Activated Carbon (GAC)
- 3 Phase Power
- pH Adjustment Chemical System
- Disinfectant Chemical System
- Corrosion Inhibitor Chemical System
- Custom Membranes

### On-Skid Mechanical Equipment:

- Low Energy High Recovery Reverse Osmosis Membranes
- Membrane Diameter: 4 in
- Frame: Carbon steel
- Permeate and Concentrate Tubing and Hose
- Concentrate Recirculation
- Pre-Filter Housing and Cartridges
- Stainless Steel Membrane Vessels
- Stainless Steel Valving, Tubing and Fittings
- On-Skid Booster Pump
- Raw and Permeate Pressure Switches
- Concentrate, Permeate, and Recycle Flow Gauges
- Concentrate, Permeate, and Recycle Pressure Gauges

### On-Skid Electrical Equipment:

- Microprocessor Controller
- 240V, Single Phase Power
- \* Electrical connections provided by others*

### Chemical Equipment:

- Anti-Scalant Dosing Pump and Integrated Tank
- \* Shipped loose*

### Installation Requirements:

- **Feed Pressure Supply Range:** 20-40 psi
- **Inlet Connection:** 3/4" NPT
- **Permeate:** 3/4" NPT
- **Concentrate:** 3/4" NPT
- **Inlet Piping:** PVC
- **Electrical Connections** (240V, 20Amp, Single Phase)

- Fiberglass Membrane Housing
- Permeate TDS and Conductivity
- Spare Set of Membranes
- Spare Cartridges
- System Set Points\*
- On-Site Commissioning and Training
- CSA Certification